

OHT / OHT_{GV}

15



OHT 15 / OHT GV 15




STANDARD AUSSTATTUNG EQUIPAGGIAMENTO DI SERIE STANDARD EQUIPMENT DE SÉRIE ACESORIOS DE SERIE




■ **HYDR. KISTENHALTER OHT / OHT GV 15 (4M)**
 ■ STRINGICARICO
 ■ LOADING BLOCK
 ■ PRESSEUR DE CHARGE
 ■ APRETON DE CARGA



■ **DREIPUNKTANBAU KAT II**
 ■ ATTACCO AL TRATTORE CAT II
 ■ 3RD POINT LINKAGE CAT II
 ■ ATTELAGE 3E POINT CAT II
 ■ CONEXION AL TRACTOR CAT II



■ **GLEITPROFIL AUS HALTBARER UND SELBSTÖLENDER ARNITQUALITÄT**
 ■ PATTINI IN ARNITE ANTISIURSA E AUTOLUBRIFICANTI
 ■ SLIDING COILS IN SPECIAL MATERIAL AGAINST USURY AND SELF-LUBRICATING
 ■ PATINS TRANSLATEUR EN MATÉRIEL SPÉCIAL AUTOLUBRIFIANT ET ANTI-USURE
 ■ PATINES EN ARNITE ANTIDESGASTE Y AUTOLUBRICANTE



■ **ZYLINDER AM 3. PUNKT**
 ■ CILINDRO 3° PUNTO
 ■ 3RD POINT CYLINDER
 ■ VÉRIN 3E POINT
 ■ CILINDRO 3° PUNTO



■ **ZUGLASCHEN**
 ■ GANCIO DI TRAINO
 ■ TOWING HOOK
 ■ CROCHET DE TRAIÑAGE
 ■ GANCHO DE REMOLQUE



■ **4 HÜBKETTEN**
 ■ 4 CATENE DI SOLLEVAMENTO
 ■ 4 LIFTING CHAINS
 ■ 4 CHAINES DE SOULEVEMENT
 ■ 4 CADENAS DE LEVANTAMIENTO



■ **SICHERHEITSVENTIL AUF HEBE- UND NEIGUNGSZYLINDER**
 ■ VALVOLA DI SICUREZZA SUL CILINDRO D'ALZATA E BRANDEGGIO
 ■ SAFETY VALVE ON LIFTING AND INCLINATION CYLINDER
 ■ SOUPE DE SÉCURITÉ SUR LE VÉRIN DE ÉLEVATION ET INCLINAISON
 ■ VALVULA DE SEGURIDAD SOBRE EL CILINDRO DE LEVANTAMIENTO Y DE INCLINACION



■ **STEUERGERÄT MIT ZUSÄTZLICHEM FUNKTIONSHEBEL (IR)**
 ■ DISTRIBUTORE PREDISPOSTO AD ULTERIORE MOVIMENTO (IR)
 ■ DISTRIBUTOR SETTED UP FOR ADDITIONAL MOVEMENT (IR)
 ■ DISTRIBUTEUR AVEC PREDISPOSITION À MOUVEMENT ADDITIONNEL (IR)
 ■ DISTRIBUIDOR PREDISPUERTO PARA MOVIMIENTO ADICIONAL (IR)



■ **KLAPPBARE UND VERSTELLBARE GABELN**
 ■ FORCHE PIEGHEVOLI E REGOLABILI
 ■ FLEXIBLE AND ADJUSTABLE FORKS
 ■ FOURCHES REPLIABLES ET REGLABLES
 ■ HORCAS PLEGABLES Y REGULABLES



■ **DANK ZU LANGEN SCHLAUCHEN, KANN MAN DIE STEUERUNG BEWEGEN**
 ■ I TUBI LUNGH PERMETTONO AL DISTRIBUTORE DI ESSERE SPOSTATO
 ■ THE DISTRIBUTOR CAN BE MOVED THANKS TO LONGER PIPES
 ■ LES TUYAUX LONG PERMETTENT AU DISTRIBUTEUR D'ÊTRE DÉPLACÉ
 ■ TUBOS LARGOS PERMITEN AL DISTRIBUIDOR DE SER DESPLAZADO

MODEL	kg	kg	mm	mm	cm	L/min
OHT 15 250 3TR	415	1500	2500	55-75	108	50
OHT 15 250 4TR	492	1500	2500	55-75	108	50
OHT 15 250 3IR	435	1500	2500	55-75	108	50
OHT 15 250 4IR	505	1500	2500	55-75	108	50
OHT GV 15 250 3TR	415	1500	2500	55-75	108	50
OHT GV 15 250 4TR	497	1500	2500	55-75	108	50
OHT GV 15 250 3IR	435	1500	2500	55-75	108	50
OHT GV 15 250 4IR	510	1500	2500	55-75	108	50
OHT 15 320 3TR	490	1500	3200	55-75	108	50
OHT 15 320 4TR	567	1500	3200	55-75	108	50
OHT 15 320 3IR	500	1500	3200	55-75	108	50
OHT 15 320 4IR	580	1500	3200	55-75	108	50
OHT 15 380 3TR	550	1500	3800	55-75	108	50
OHT 15 380 4TR	627	1500	3800	55-75	108	50
OHT 15 380 3IR	560	1500	3800	55-75	108	50
OHT 15 380 4IR	640	1500	3800	55-75	108	50
OHT 15 450 3TR	620	1500	4500	55-75	108	50
OHT 15 450 4TR	697	1500	4500	55-75	108	50
OHT 15 450 3IR	630	1500	4500	55-75	108	50
OHT 15 450 4IR	710	1500	4500	55-75	108	50